Find us on: Facebook, Google+ & YouTube

METALSHOP MADNESS Spring & Summer 2018









STATIONARY 6.5 PEAK HP **60 GALLON** AIR COMPRESSOR

KC-6160V1

- 150 PSI max pressure
- 13.4 CFM @ 40 PSI
- 11.2 CFM @ 90 PSI

• High efficiency reed valves



 Two powerful 3/4 HP 110V motors Lathe chuck and drill chuck safety guards with limit switch protection and standard tool post safety guard Comes with 5"- 3 jaw chuck, imperial & metric change gears, quick change tool post with 1/2" capacity, steady rest, follow rest, thread chasing dial indicator, MT#3 & MT#4 dead centres, 5 cutters, 1/2" drill chuck and tool box with adjusting tools





The Most **Innovative Drill Press EVER!**

DVR with Adaptive Control™ Software

18" NOVA VOYAGER **DVR DRILL PRESS** 58000 BY: KING INDUSTRIAL

- Powerful direct drive 1.75 HP high torque motor
- with no pulleys or belts to cause vibration
- Spindle taper MT #2
- Digital Variable Reluctance (DVR) Direct Drive Technology with Adaptive ControlTM Software
- Comes with 5/8" drill chuck & key, firmware USB cable, knock-out wedge, adjustment wrench and hex. keys



NEW

⊕

RETRAGIABUSAIR HOSE REELWITH HYBRID

POLYMERAIR HOSE K-5038FRL

50 ft. x 3/8"

All-Weather Flexibility (-40°C to 65°C)
 Comes with wall mounting hardware

MANUALAIR LOSE REEL WILL LIMBRID POLYMERAIR HOSE K-10014FRL

100 ft. x 1/4"

All-Weather Flexibility (-40°C to 65°C)

INCLUDED WITH THE PURCHASE OF A

Includes: angle drill press vise, drill chuck

O MILLING DRILLING MACHINE

360° swivel base





NEW KM-124 **Elevating block with 7/16"** T-slots (7-7/8" x 5-7/8" x 5")

ARCHIC EUSX

	عاست
A COUNTY	A
A CONTRACTOR OF THE PARTY OF TH	(F40'G
AROTIC FLOR	(40°C)
CONTRACTOR OF THE PARTY OF THE	(55G)
THE RESERVE OF THE PARTY OF THE	
37	
AAA DOLAHAWAAAA	
300 PSI MAXIMUM	PRESSURE

	BRID POLY <i>N</i> TRIAL AIR H	
K-2514H	25'x1/4"	\$19.99
K-2538H	25'x3/8"	\$26.99
K-5014H	50'x1/4"	\$29.99
K-5038H	50'x3/8"	\$39.99
K-10014H	100'x1/4"	\$49.99
K-10038H	100'x3/8"	\$59.99

ALLWEATHER HEAVY-DUTY EXTENSION CORDS Length AWG Color 12/3 YELLOW K-2512-1T-RD 25' 12/3 RFD 23.99 25' 12/3 ORANGE 15A 125V, 1675W For indoor and outdoor use Ultra flexible / High visibility colors / Lighted ends 12/3 12/3 5012-1T-RD RED 12/3 12/3 ORANGE GREEN CORD **EXTENSION** 12/3 RED

29 PC. TITANIUM DRILL BIT SET KDB-29T 17" DRILL PRESS

17" DRILL PRESS with SAFETY **GUARD & LIMIT SWITCH**

with key, drill chuck arbor, carbide tipped face mill and face mill arbor 7" X 12" METAL CUTTING BANDSAW

5 PC. ACCESSORY BONUS PACKAGE FREE



(S) NAME SANSON	H.S.S. & BI-METAL BLADES ("SKIP TOOTH")						
The state of the s	Model	Length	Width	Blade Material	TPI	Thickness	Price
	KBB-712-10	93"	3/4"	H.S.S.	10	.032"	\$19.99
(KBB-712-14	93"	3/4"	H.S.S.	14	.032"	\$19.99
Acceptance of	KBB-712-18	93"	3/4"	H.S.S.	18		\$19.99
1	KBB-712-BM-610	93"	3/4"	Bi-Metal	6-10	.032"	\$59.99
	KBB-712-BM-1014	93"	3/4"	Bi-Metal	10-14	.032"	\$59.99

MILLING DRILLING MACHINE with **SAFETY GUARD & LIMIT SWITCH** PDM-30 • 16 1/2" swing

• 1 1/4" Drilling capacity

• 3" Face mill capacity

• 5" stroke • Spindle taper R8

• 12 speeds (150-2500 RPM)



MILLING **DRILLING MACHINE STAND**

SS-45

Heavy-duty steel construction







AIR COMPRESSORS **10 GALLON 6.5 HP GAS WHEELBARROW** AIR COMPRESSOR KC-6510G1 150 PSI max pressure 14.1 SCFM @ 40 PSI 11.2 SCFM @ 100 PSI NAME AND ADDRESS OF THE OWNER, WHEN PERSON NAME AND ADDRESS OF THE O ASME safety valve High efficiency reed valves 11.2 20世 章 90 四年/197 150 8年日 for maximum performance **COMPRESSOR 5.5 PEAK HP 20 GALLON** AIR COMPRESSOR



Extreme All-Weather Flexibility Kink resistant

PREMIUM/HYBRID POLYMER

Walder Double filtration system

12 ft. power cord

K-5058GH $5/8" \times 50 \text{ ft.}$

\$39.99

K-10058GH

Comes complete with 6 ft. x 1-1/4" hose, 2 pc. plastic extension wand, 30L dust bag, cartridge filter, foam filter, reusable filter, 10" floor sweep and crevice tool





8540LST
• 12 ft. power cord
• Comes complete with 6 ft. x 1-1/4" hose, 2 pc. extension wand, 40L dust bag, cartridge filter, foam filter, reusable filter, 10" floor sweep and crevice tool



5 PEAK 1040 LITERS GALLON US

8560LST

Comes

starter

with magnetic

18 ft. power cord
Comes complete with 8 ft. x 2-1/2" flex hose, 2 pc. 2-1/2" extension wand, contoured handle with air control, cartridge filter, foam filter, 14" floor sweep with squeegee insert, gulper tool, crevice tool and hanging accessory storage bag



6.5 PEAK 1660 LITERS GALLON US

HEPA CARTRIDGE FILTER

KVAC-1145

KVAC-1150 Fits: 8560LST 8531LP-B, 8540LST, \$29,99 **S29**

OIL BOTTLE KW-077 KC-2051H1 (850ml) • 150 PSI max pressure • 7.6 SCFM @ 40 PSI • 6.0 SCFM @ 90 PSI TIRE INFLATION **GUN WITH PRESSURE GAUGE** K-1630 KING



Z(0) (\circ)



5.5 PEAK HP 24 GALLON AIR COMPRESSOR

KING

KC-3124V1

- 150 PSI max pressure
- 7.6 CFM @ 40 PSI
- 6.0 CFM @ 90 PSI









HIGH OUTPUT 6.5 PEAK HP **60 GALLON AIR COMPRESSOR**

KC-5160V1

- 150 PSI max pressure
- 22.6 SCFM @ 40 PSI
- 18.5 SCFM @ 100 PSI
- High efficiency reed valves





18.5 OF# = 100 :

HIGH OUTPUT 7.5 PEAK HP **80 GALLON AIR** COMPRESSOR

KC-7180V1-MS

- · High output 30 CFM @ 100 PSI
- 150 PSI max pressure
- 43 SCFM @ 40 PSI

• 30 SCFM @ 100 PSI

ASME safety valve

7/1 PGAIRTOOLKII

8171

Comes with 1/2" Impact, Wrench, 3/8" Ratchet Wrench Air Hammer and 1/4



SFRAY GUN KITS 8180 8182 8185







8190

HVLP

KING







ASME safety valve

8195

METAL FORMING MACHINES





ARBOR PRESS

KAP-3

 Precision cut steel rams and pinions for accurate operation

- Capacity: 3 Ton • Diameter of work: 12 1/2"
- Capacity over table: 12"

COMBINATION ROTARY

MACHINE KC-RM22

Cutting capacity (mild steel): 22 Gauge
Distance between shaft centers: 2"

Depth of throat to frame: 7

• Includes 6 dies for hooking (2), burring, wiring, ogee beads and crimping

\$699.



Bending length 48"Capacity 12 GaugeWeight 1140 lbs

HAND SHEAR

12"

KC-HS12

- · Level arm with
- compensating spring
 Easy cutting across the entire length
- Rigid cutter body

\$199.99

4 TON HAND NOTCHER

KC-N616

- Heavy cast-iron construction
- 16 Gauge notching capacity (mild steel)
- 18 Gauge piercing capacity (mild steel)
- Maximum notch
- (6" X 6" x 90°)
- Weight 165 lbs

\$699

SLIP ROLLS

KC-S5016

- Max. length 50"Capacity 16 GaugeWeight 50 lbs

KC-S3622

- Max. length 36"Capacity 22 Gauge
- Weight 176 lbs

659

KC-S2422

- Max. length 24"Capacity 22 Gauge
- Weight 81 lbs



SHEAR, BRAKE AND ROLL

KC-1220

- Max. length 12"
- Maximum thickness
- 20 Gauge Weight 95 lbs

\$459.

KC-3020

- Max. length 30"
- Maximum thickness 20 Gauge
- Weight 300 lbs

0)7/

KC-4020

- Max. length 40"
- Maximum thickness 20 Gauge
- Weight 387 lbs



METAL FORMING MACHINES



POWER TOOLS & AU

3" X 79" METAL BELT SANDER KC-379MS

- Sanding belt rotates on 7-1/2" vented drive wheel and solid rubber rear wheel for maximum tracking and sanding control · Head pivots up or down on base for easy and safe work heights
- Horizontal working height of 36"
- Comes with 80 Grit pure zirconia sanding belt

12" HEAVY-DUTY BENCH GRINDER WITH FLOOR STAND

KC-1295

- Robust cast-iron wheel guards and dust vents with 2-1/2" T-fitting adaptor for dust collection Comes complete with floor stand, built-in cast-iron
- quench tray, 36 Grit and 60 Grit 12" x 2" grinding





3"x 79" PURE ZIRCONIA SANDING BELTS				
Model	Belt Size	Grit	Unit	Price
SB-379-60	3"x79"	60	1	\$17.99
SB-379-80	3"x79"	80	1	\$17.99
SB-379-120	3"x79"	120	1	\$17.99

28 METAL DUST COLLEGIOR

KC-7300C

- Powerful 2 HP, 220V motor
- 2 Step activation safety switch with line voltage interruption in case of power failure
- Ideal for collection of metal chips and abrasive dust produced by metal sanders, grinders, cold cut saws, deburring and chamfering machines
- Large metal chips colection drawer is easy to access and clean
- 6" inlet with Y-inlet adaptor with two 3" dust inlets allowing up to connect up to two metalworking machines
- · Comes with large paper filter





KMAG-220-811 220V (8-11 Amp.) KMAG-220-1114 220V (11-14 Amp.) KMAG-220-1417 220V (14-17 Amp.) KMAG-220-1721 220V (17-21 Amp.)



Comes with padlock and 2 spare keys

FIREPROOF 3"METAL DUST **COLLECTION HOSES KIT**

KM-102

Kits Includes

2 - 8ft. (2.5M) 130°) Fireproof hoses

4 - Wire hose clamps (3")

3" WIRE HOSE



CLAMP

K-1316







DIGITAL FRACTIONAL CALIPER

KM-106

Converts to inches (decimal and fractional) and metric readings

Waterproof to IP54 standards • Two 3V Lithium batteries included











12" X 36" GEARHEAD METAL LATHE 口识用

- Comes complete with 6"-3 jaw chuck, 8"-4 jaw chuck, imperial and metric gears, quick change tool post, steady rest, follow rest, 10" DI-4 camlock face plate, thread chasing dial indicator, MT#3 dead center, MT#3 arbor taper, 1/2" drill chuck, full length splash guard, tool box, chuck keys and hex. keys



14" X 40" GEARHEAD METAL LATHE

Comes complete with 6"-3 jaw chuck, 8"-4 jaw chuck, replacen gears, quick change tool post, steady rest, follow rest, 12" DI-4 camlock face plate, coolant system, full length splash guard, thread chasing dial indicator, 2 MT#3 dead centers, JT#5-MT#3 sleeve, chip tray, tool box, halogen lamp, chuck keys, hex. keys, and cabinet stand with foot brake

KC-1440ML-6 649

WITH TAPER ATTACHMENT KC-1440ML-6/KM-054

Θ

16" X 40" HIGH PRECISION "TOOL ROOM" METAL LATHE

- Spindle speeds 16(45-1800 RPM)
- 2" spindle bore diameter
- 45(2-72 T.P.I) thread cutting
- Comes complete with 8"-3 jaw chuck with inside & outside jaws 12"-4 jaw chuck, quick change tool post and two 3/4" tool holders, steady and follow rests with roller guides, 14" (D1-6) camlock face plate, MT #4 standard dead centre, MT #4 carbide tipped dead centre, MT #4 to MT #6 spindle sleeve adapter, halogen light, coolant system, full length splash guard, manual micrometer carriage stop, tool box and wrenches

KC-1640ML

WITH TAPER ATTACHMENT KC-1640ML/KM-055

Θ

16" X 60" GEARHEAD ENGINE LATHE KC-1660GH

- Spindle speeds 16(33-2000 RPM)
- 2 1/16" Spindle bore diameter
- 4-56 T.P.I. thread cutting
- Comes complete with 8"-3 jaw chuck with inside & outside jaws, 10"-4 jaw chuck, quick adjust 6-way tool post, steady rest, follow rest, 14" (D1-6) camlock face plate, taper attachment, 1 live center MT #4, 2 dead centers MT#4 & MT #6, thread chasing dial, metric and imperial dials, halogen light, coolant system, full length splash guard, 4 positions cross slide stop, cabinet stand

incorporated) and a tool box





7



(full length with foot brake



These Taper Attachments are designed

to fit our 12" x 36", 14" x 40" & 16" x 40"

Metal Lathes models

KC-1236ML, KC-1440ML-6 & KC-1640ML

7 PC. QUICK CHANGE

KQCT-0012 Fits most lathes up to 0 to 12" swing

KQCT-1015

between 10" to 15" swing

KQCT-1318 Fits most lathes between 13" to 18" swing

FAGOR DIGITAL READOUT SYSTEM



20i-T-1040

20i-T-1260 2/AXIS with

METAL CUTTING BANDSAWS

5" x 6" METAL CUTTING BANDSAW

KC-129C

- 3 speeds (80-120-200 FPM)
- Comes with wheels for portability



5" x 6" DUAL SWIVEL METAL CUTTING BANDSAW KC-129DS • Head swivels 0° - 45° to the right and 0° - 60° to the left • Adjustable hydraulic downfeed control • Automatic shut-off switch • Adjustable ball bearing guides • Portable design for easy movement COUSTANDS LYDRAUGS SAMPS (110V)

10" x 18" METAL CUTTING BANDSAW

KC-227-2 (220V) KC-227-6 (600V)

- 4 speeds (114, 196, 288, 377 FPM)
- Carbide ball bearing blade guide
- Centralized control panel and automatic shut-off
- Adjustable hydraulic downfeed control
- To ensure reliable accurate cuts, both adjustable control arms can be positioned as close to the cut as possible.



Length Width TPI Thickness Price

10" x 18" VARIABLE SPEED SWIVEL METAL CUTTING BANDSAW

KC-228S-V-2 (220V) KC-228S-V-6 (600V)

- Variable Speeds (73-312 FPM)
- Carbide ball bearing blade guides
- Adjustable hydraulic downfeed control
- Swivel base from 0° to 45°
- Coolant system with regulator valves provide an even flow of coolant to the blade

\$5999.

Length Width TPI Thickness Price

H.S.S. BLADES







METAL CUTTING BANDSAWS

7" x 12" METAL CUTTING BANDSAW WITH GEAR DRIVE

KC-712GH-5

- Returning coolant system3(110-230-340 FPM)
- · Automatic shut-off
- Adjustable ball bearing guides

PATENTED GEAR DRIVE SYSTEM....

is the ONLY one in the Canadian market which allows the user to change speeds without stopping the machine.



$7'' \times 12''$ DUAL SWIVEL METAL CUTTING BANDSAW KC-712DS

- Returning coolant system4 speeds (98-164-246-328 FPM)
- Automatic shut-off
- Adjustable ball bearing guides



9"x 18" METAL CUTTING **SWIVEL BANDSAW**

KC-918S-V

- Speeds (80-250 FPM)
- · Carbide ball bearing blade guides with rollers
- · Centralized control panel and automatic shut-off
- Adjustable hydraulic downfeed control
- Precision blade tension adjustment
- Head swivels 0° to 45° in one direction





17" VARIABLE SPEED METAL/WOOD CUTTING **BANDSAW**

KC-1700WM-VS

- Variable speeds (wood): 540-3600 SFPM
 Variable speeds (metal): 100-650 SFPM

- Voltage (input power): 220V, 1 phase, 60 Hz
 Comes with a 1/2" x 6 TPI wood cutting blade, 1/2" x 10 TPI metal cutting blade, laser guide, work lamp, miter gauge and a precision "TRU-RIP" aluminum rip fence with resaw guide



18" METAL CUTTING **BANDSAW**

6 Amp.

(220V)

KC-450

- Variable speed
- Handwheel controls speedSpeed changes while the machine is in operation
- Comes complete with 4-way tilting table, and







CLEAR PVC REINFORCED SUCTION HOSES

FLAT PVC DISCHARGE HOSES



KW-252 KW-253 2" X 25 ft 3" X 25 ft

KW-503 KW-502 3" X 50 ft 2" X 50 ft

PORTABLE WARNABLE SPEED

14"CUT-OFF SAW

- Standard 14" abrasive wheel for cutting ferrous metal
- Quick release vise for holding workpiece, which allows cuts up to a 45° angle



(15 Amp. Motor)

3 postion control handle

INSPECTION CAMERA WITH LCD MONITOR

KC-9050

Kit includes:

· Camera handle, 9mm dia. x 39"

flexible camera probe

• 2.4" diagonal TFT-LCD color monitor,

Kit comes with 3 accessory tools (45° mirror, magnetic pick-up, pick-up hook) and 4 AA batteries

JUMP STARTER / **PERSONAL POWER SUPPLY**

- Charge or power all electronic
- & power supply is able to jumpstart a V8 engine (5L) up to 15 times.

devices, USB 5V electronics, 12V accessories and 16V/19V laptops.
This 13,600 mAh portable jump starter Nylon wheels \bigcirc





CARS, BOATS MOTORCYCLES AND TRUCKS



POWER OR CHARGE ELECTRONIC DEVICES





4.5MM CAMERA PROBE FOR **INSPECTION CAMERAS** KW-9123 4.5mm diameter x 39" flexible-obedient camera probe waterproof to IP67 standards · LED lights inside the

camera probe tip illuminate dark spaces

10

WITH RECORDABLE **LCD MONITOR** KC-9200 DIGITAL Camera handle, ZOOM 39"x 9mm camera probe. 39" x 10mm camera probe extension, 3.5" TFT-LCD wireless color 99.99 monitor, monitor Li-ion charger, 3 accessory tools (45° mirror, magnetic pick-up, pick-up hook),USB and Video cables, 4GB SD

memory card and 4 AA batteries

WIRELESS INSPECTION CAMERA

2000WGASOUNE

KCG-2001i

- Sine wave digital inverter generator
- provides stable current to power voltage-sentitive electronics
- Powerful 3 HP, 4 stroke air cooled OHV engine DC output for charging smartphones, tablettes or any USB powered equipment
- DC Cigarette Lighter Socket: 12V/8 Amp DC output AC Duplex Outlet 120V/13.3 Amp

USB C

AC output



GENERATOR EXTENSION CORDS

Converts a Nema L14-30P 240V 30 Amp Twist Lock plug into Nema 5-15/20R 120V 20A receptacles

K-L1430-10

Extension cord length: 10 feet Gauge (AWG)/Cord: 12 (SJTW 4/C) Number of 120V plugs: 4

K-L1430R-25

Extension cord length: 25 Gauge (AWG)/Cord: 10 (SJTW 4/C) Number of 120V plugs: 4

K-L1430-25-4T

Extension cord length: 25 fee Gauge (AWG)/Cord: 10 (ŠITW 4/C) Number of 120V plugs: 4



Resets

RVGENERATOR ADAPTER

K-TT30R

This adapter allows a generator with a NEMA L5-30R 125V twist lock receptacle to be connected to recreational vehicles that use typical RV extension cords



PRESSURE WASHER

- KPW-3001FM 3000 PSI, 2.3 GPM maximum
- Thermal relief valve on pump to
- protect against overheating 25' high pressure hose and inlet hose quick connect coupling
- Comes with 10" pneumatic wheels for portability and 4 quick connect nozzles (0°, 15°, 25°, 40°



PORTABLE & CASOLINE GENERATORS













950W PORTABLE GENERATOR

KCG-951G

- Powerful 2 HP, 2 stroke air cooled motor
- Brushless alternator and electronic ignition
- Outlet: 120V/6.7 Amp AC output
- Outlet: 12V/5.3 Amp DC output
- · Easy start manual recoil starter
- AC and DC circuit breakers and reset buttons for safe operation
- · Comes with DC cables and spark plug socket

1500W GASOLINE GENERATOR

KCG-1501GN

- Powerful 3 HP, 4 stroke air cooled motor
- Electronic ignition
- · Low oil shut-off with indicator light protects the engine
- Duplex Outlet: 120V/10 Amp. AC output
- Terminals: 12V, 8 amp. DC output
- Easy start recoil starter
- AC and DC circuit breakers for safe operation
- Comes with DC cables and spark plug socket

4200W GASOLINE GENERATOR WITH WHEEL KIT

KCG-4200G

- Powerful 7 HP, 4 stroke air cooled motor
- AVR system and electronic ignition
- · Low oil shut-off with indicator light protects the engine
- Duplex outlet: 120V/20 Amp AC
 Twist lock outlet: 120V/240V/30 Amp AC
- · Easy start recoil starter
- · Voltage switch and ground terminal
- AC double throw circuit breaker and resets for safe operation
- Wheel kit includes 8" wheels and pivot handle

6500W GASOLINE GENERATOR WITH WHEEL KIT

KCG-6501G

- Powerful 15 HP. 4 stroke air cooled motor
- AVR system and electronic ignition
- Low oil shut-off with indicator light protects the engine
- Duplex outlet: 120V/20 Amp AC
- Twist lock outlet: 120V/240V/30 Amp AC
- AC double throw circuit breaker and resets for safe operation

8500W GASOLINE GENERATOR WITH ELECTRIC START & WHEEL KIT

KCG-8500GE

- Powerful 15 HP, 4 stroke air cooled motor
- AVR system and electronic ignition
- Two duplex outlets: 120V/20 Amp AC
- Two twist lock outlets: 120V/30 Amp and 120V/240V/30 Amp AC

10000W GASOLINE GENERATOR WITH ELECTRIC START & WHEEL KIT

KCG-10000GE

- Powerful 15 HP, 4 stroke air cooled motor
- AVR system and electronic ignition
- · Low oil shut-off with indicator light protects the engine
- Two duplex outlets: 120V/20 Amp AC
- Two twist lock outlets: 120V/30 Amp and 120V/240V/30 Amp AC
- Keyed electric start and easy start recoil starter
- · AC double throw circuit breaker

